



Industrie Service

# Attestation of TA-LUFT VDI2440

Attestation No.:250799 Rev.1

Ref. report No. :250800 Rev.1

**Manufacturer** : Antiwear (Suzhou) Industrial Intelligent Technology Co., Ltd.

**Postal address of manufacturer** :No.988, Yuexiu Road, Fenhui Economic Development Zone,

**PC**: 215200, Suzhou City, Jiangsu Province, P. R. China

## Tested Product Description:

<b>Item</b>	AB-8F9RF-C-CG258 Ball Valve
<b>Valve size (DN)</b>	8"
<b>Pressure rating</b>	Class 900
<b>Stem size</b>	Φ79.8 mm
<b>Body/bonnet material</b>	ASTM A216 WCB
<b>Seal material</b>	Flexible Graphite
<b>Valve assembly drawing no.</b>	A005284 VER. 1.0

## Test Condition:

Testing principles are according to Technical Instructions on Air Quality Control-TA Luft (July 2002) and VDI guideline 2440 (November 2000) and the key test conditions have been specified according to the following information:

<b>Test Fluid</b>	Helium	
<b>Test Temperature(°C)</b>	Room Temperature	200°C
<b>Test Pressure(bar):</b>	154	132
<b>No. of Switching Cycles</b>	205	
<b>Specific Leakage Rate <math>\lambda</math> mbar·l/(s·m)</b>	$\lambda \leq 10^{-4}$	

Hereby, It is certified that the tested valve of the above mentioned company have been tested and the test results are accepted according to above mentioned specification. Details could be taken from the associated report with the No.:250800 Rev.1

**Shanghai, August 31, 2022**  
(Place, date)

*Chen Guilin*  
**Guilin Chen**  
**TÜV SÜD Industrie Service GmbH**

Westendstr. 199  
80686 München Germany

TÜV SÜD Industrie Service GmbH  
Shanghai Office  
Floor 3-13, No.151, Heng Tong Road,  
Shanghai 200070 P. R. China

Tel.: +86 21 6141-0123  
Fax: + 86 21 6140-8600



Industrie Service

Choose certainty.  
Add value.

**TÜV SÜD**  
**Industrie**  
**Service GmbH**  
**Shanghai Office**

## REPORT OF THIRD PARTY INSPECTION

Client: Antiwear (Suzhou) Industrial Intelligent Technology Co., Ltd.

No.988, Yuexiu Road, Fenhui Economic Development Zone,

PC: 215200, Suzhou City, Jiangsu Province, P. R. China

Contact Person: Mr. Wu Bin

Manufacturer Name: Antiwear (Suzhou) Industrial Intelligent Technology

Co., Ltd.

No.988, Yuexiu Road, Fenhui Economic Development Zone,

PC: 215200, Suzhou City, Jiangsu Province, P. R. China

Inspection Place: Hefei General Machinery & Electrical Products Inspection

Institute National Quality Supervision and Inspection Centre of Pump and Valve  
Products

Contact Person: Mr. Wu Bin

Inspection Date: May 22~24, 2017

Inspector: Chen Guilin

Quality System Status: Acceptable

Order Number: 7482135944

No. 151, Heng Tong Road  
Shanghai 200070,  
P.R.China  
Telefon: +86 21 6141 0123  
Telefax: +86 21 6140 8600  
Internet: [www.tuvsud.com](http://www.tuvsud.com)  
E-mail: [guilin.chen@tuvsud.com](mailto:guilin.chen@tuvsud.com)

Excerpts from this document  
August only be reproduced and  
used for advertising purposes with  
the express written approval of  
TÜV SÜD Industrie Service GmbH

The test results refer exclusively  
to the units under test.

Inspection-No.: 250800 Rev.1

## 1. Witness relevant tests

### Nature Of Inspection:

This is to report that we, TÜV SÜD Industry Service GmbH Shanghai Office on May. 22~24, 2017 at the request of Antiwear (Suzhou) Industrial Intelligent Technology Co., Ltd. conducted the following inspection:

### 1. Witness relevant tests

#### 1.1 General Information

Antiwear (Suzhou) Industrial Intelligent Technology Co., Ltd. commissioned us to witness valve fugitive emission test according to TA-LUFT 2002, Sec. 5.2.6.3 & 5.2.6.4, guideline VDI 2440 Nov.2000, Sec. 3.3.1.3 & 3.3.1.4 to verify whether the test result can meet the specific leakage rate according to the German Clean Air Act( $\lambda \leq 10^{-4}$  mbar·l/(s·m)) and for the test valve the leakage is  $\leq 2.50 \times 10^{-5}$  mbar.l/s.

#### 1.2 Tested Product Description:

The test samples have been chosen and the details of test samples can be seen in the following information. Details of the test sample can be seen in the annex.

Item	AB-8F9RF-C-CG258 Ball Valve	
Valve size	8"	
Pressure rating	Class 900	
Stem size	Φ79.8 mm	
Body/bonnet material	ASTM A216 WCB	
Seal material	Flexible Graphite	
Valve assembly drawing no.	A005284 VER. 1.0	

#### 1.3 Test Condition:

The test has been referred to the method of ISO15848-2015 annex A and carried out according to the requirements of the customer. The key test conditions have been specified according to the following information:

Test Fluid	Helium	
Test Temperature(°C)	Room Temperature	200°C
Test Pressure(bar):	154	132
No. of Switching Cycles	205	

#### 1.4 Visual and dimensional check of the test valve:

The test valve was chosen at random by the manufacturer in its workshop and submitted to the laboratory. The visual and dimensional check was performed according to drawing No.: A005284 VER. 1.0 and results found satisfactory.

#### 1.5 Preparation of the test valve

Before the fugitive emission test, the test valve was hydrostatic tested under 270bar, the test showed no visible leakage or deformation. Then the valve was cleaned and dried.

#### 1.6 Calibration of test instrument

Inspection-No.: 250800 Rev.1

The test instrument was turned on, warmed up according to the requirements of the equipment manufacturer and calibrated with the standard.

### 1.7 Fugitive emission test and measurement

The test valve was mounted on a test rig with the stem positioned vertical. And the fugitive emission test is carried out according to above mentioned requirements.

#### 1.7.1 Preliminary tests at room temperature

The valve was pressurized with test fluid Helium to 15.4MPa according to manufacturer's requirements in the partly opened position, the temperature is measured and recorded as room temperature.

The test results are as follows and details can be seen in the annex:

##### Test results of preliminary tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$2.6 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.2 Mechanical cycle test at the room temperature

A total of 50 mechanical cycles was performed on the test valve while it was kept pressurized under a differential pressure of 15.4MPa according to the manufacturer's requirements at room temperature. The pressure should be improved and kept at 15.4MPa to measure the leakage, and then the leakage from the stem seal is measured with following results and details can be seen in the annex:

##### Test results of final tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$3.6 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.3 Static test at the selected test temperature

The test valve was heated till to 200°C. The test valve was kept pressurized with 13.2MPa according to manufacturer's requirements at the temperature between 185 and 215°C. The leakage from the stem seal were measured with following results:

##### Test results of final tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$6.0 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.4 Mechanical cycle test at the selected temperature

A total of 50 mechanical cycles was performed on the test valve while it was kept pressurized with 13.2MPa according to manufacturer's requirements at the temperature between 185 and 215°C. The leakage from the stem seal was measured with following results:

##### Test results of final tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$4.8 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.5 Intermediate static test at the room temperature

Inspection-No.: 250800 Rev.1

The test valve returned to the room temperature naturally, without artificial cooling/heating. After the temperature was stabilized at room temperature. Then the stem seal leakage under 15.4MPa according to manufacturer's requirements was measured using the same method as mentioned above, with following test result:

Test results of final tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$6.0 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.6 Repeat of mechanical cycle test at the room temperature

A total of 50 mechanical cycles was performed on the test valve while it was kept pressurized with 15.4MPa according to manufacturer's requirements at room temperature. The leakage from the stem seal was measured with following results:

Test results of final tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$6.2 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.7 Repeat of static test at the selected test temperature

The test valve was heated till to 200°C. The test valve was kept pressurized with 13.2MPa according to manufacturer's requirements at the temperature between 185 and 215°C. The leakage from the stem seal were measured with following results:

Test results of final tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$6.4 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.8 Repeat of Mechanical cycle test at the selected temperature

A total of 50 mechanical cycles was performed on the test valve while it was kept pressurized with 13.2MPa according to manufacturer's requirements at the temperature between 185 and 215°C. The leakage from the stem seal was measured with following results:

Test results of final tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$6.1 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.9 Intermediate static test at the room temperature

The test valve returned to the room temperature naturally, without artificial cooling/heating. After the temperature was stabilized at room temperature, The leakage from the stem seal was measured with following results while it was kept pressurized with 15.4MPa:

Test results of final tests

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$6.2 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.10 Final test at the room temperature

Inspection-No.: 250800 Rev.1

A total of 5 mechanical cycles was performed on the test valve while it was kept pressurized with 1.96MPa. The leakage from the stem seal under 15.4MPa according to manufacturer's requirements was measured with following results:

Test results of final tests at room temperature (test 6)

Item	Required Value	Actual Value
Stem leakage (mbar.l/s)	$\leq 2.50 \times 10^{-5}$	$5.9 \times 10^{-6}$

The test results meet the requirements of VDI2440 Nov.2000.

#### 1.7.11 Post test examination

After all the above tests completed, the test valve was disassembled and all sealing components visually examined. It is found that no notable wear and any other significant observations.

We, hereby declare that the inspector has checked test valve and witnessed the fugitive emission test on the tested valve. The test results are as mentioned in this report.

Annex:

Annex 1: Drawings with assembly drawing No. A005284 VER. 1.0;

Annex 2: Test Report of Fugitive Emission Test No. 2017FM295;

  


Inspected by: Chen Guilin

Date of issue: August 31, 2022