

# CERTIFICATE

## according to IEC EN 61508

Certificate No.: TUV IT 23 SIL 0193

**CERTIFICATE OWNER:** Antiwear (Suzhou) Industrial Intelligent Technology Co., Ltd.

No.988, Yuexiu Road,

Fenhu Economic Development Zone,

PC: 215200, Suzhou City,

Jiangsu Province,

P. R. China

## WE HEREWITH CONFIRM THAT AB SERIES SSB SOFT SEALED BALL VALVES MEET THE SIL REQUIREMENTS DETAILED IN THE ANNEXED TABLE

#### FOR THE SAFETY FUNCTIONS:

SIF1: "correct switching on demand (open to closed) and tight for closing phase, in low demand mode of operation"

SIF2: "correct switching on demand (closed to open), in low demand mode of operation"

The above reported AB Series SSB Soft Sealed Ball **Examination result:** 

> Valves were found to meet the standard defined requirements of the safety levels detailed in the following table according to IEC EN 61508, under fulfillment of the conditions listed in the Report R TUV

IT 23 SIL 0181, on which this Certificate is based

Construction/Functional characteristics and reliability **Examination parameters:** 

and availability parameters of the above mentioned AB

Series SSB Soft Sealed Ball Valves

R TUV IT 22 SIL 0181 Official Report No.:

March, 22th 2026 **Expiry Date** 

IEC EN 61508:2010 Part 2, 4, 6, 7 Reference Standard

Milan, March, 23<sup>rd</sup> 2023

**TÜV ITALIA Srl** 

TÜV ITALIA Srl Industrie Service Division

Alberto Carelli

**Managing Director** 



### SUMMARY TABLE



Italia

E/EE/EP safety-related system (final element)	AB Series SSB Soft Sealed Ball Valves produced by Antiwear (Suzhou) Industrial Intelligent Technology Co., Ltd.	
System type	Type A	
Systematic Capability	SC3	
Safety Function Definition	SIF1: "Correct switching on demand (open to closed) and tight for closing phase, in low demand mode of operation"	SIF2: "Correct switching on demand (closed to open), in low demand mode of operation"
Max SIL <sup>(1)</sup>	SIL3	SIL3
$\lambda_{TOT}$	2,316E-08	2,316E-08
$\lambda_{NE}$	5,542E-09	7,924E-09
$\lambda_{\mathbf{S}}$	0,000E+00	0,000E+00
$\lambda_{\mathrm{DD,PST}^{(2)}}$	4,699E-09	1,121E-08
λ <sub>DU,FPT</sub>	1,292E-08	4,023E-09
$\beta$ and $\beta_D$ factor	10%	10%
MRT	8 h	8 h
Hardware Safety Integrity	Route 2 <sub>H</sub>	Route 2 <sub>H</sub>
Systematic Safety Integrity	Route 2s	Route 2 <sub>S</sub>

#### Remarks

(1) The Safety Integrity Level (SIL) of the entire Safety Instrumented Function (SIF) must be verified via a calculation of  $PFD_{AVG}$  considering the redundant architectures, proof test interval, proof test effectiveness, any automatic diagnostics, average repair time and the specific failure rates of all products included in the SIF. Each subsystem must be checked to assure compliance with the minimum hardware fault tolerance (HFT) requirements.

(2) Considering an automatic Partial Stroke Test.

SIL classification according to Standard IEC EN 61508:2010 for AB Series SSB Soft Sealed Ball Valves produced by Antiwear (Suzhou) Industrial Intelligent Technology Co., Ltd.

NOTE: The present table is integral part of the Document TUV IT 23 SIL 0193 Date: March, 23<sup>rd</sup> 2023